

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Overall Wash

Recommended Use: Heavy Duty Laundering. Greasy clothing

Supplier: Midland Chemicals
ABN: 91 622 018 986

Street Address: 18 Elliott Street
Midvale
Western Australia

Telephone Number: +61 08 9274 1992

Facsimile: +61 08 9250 1710

Emergency Telephone: **1 800 033 111 (ALL HOURS)**

2. HAZARDS IDENTIFICATION

Hazardous according to the criteria of ASCC [NOHSC:1008(2004)]

Road and Rail; Dangerous Goods according to the criteria of the Australian Dangerous Goods Code (ADG Code).

Risk Phrases: R35: causes severe burns.
R36: Irritating to eyes.
R37: Irritating to skin.
R38: Irritating to respiratory system.

Safety Phrases: S2: Keep out of reach of children.
S3: Keep in a cool place.
S13: Keep away from food, drink and animal foodstuffs.
S14: Keep away from acids, and ammonium salts and other Class 8 corrosive substances.
S23: Do not breathe gas/fumes/vapour/spray
S24/25: Avoid contact with skin and eyes
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S27/28: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.
S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.
S45: In case of accident or if you feel unwell seek medical advice immediately (show label where possible)
S46: If swallowed, seek medical advice immediately and show this container or label.

Poisons Schedule: 6

Packaging group number: III

MATERIAL SAFETY DATA SHEET

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Sodium Hydroxide (NACID)	1310-73-2	12%	R36, R37,R38
Alkaline salts		85%	
Inert Non Hazardous Products		2%	
Biodegradable Surfactant Non Hazardous		1%	

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor at once.

Inhalation:

Remove from contaminated area immediately; avoid becoming a casualty. Put in comfortable position loosen any clothing. Seek immediate medical attention.

Skin Contact:

If spilt on skin or hair, immediately drench with running water and remove contaminated clothing. Wash affected areas thoroughly with water. Seek immediate medical advice.

Eye Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Seek immediate medical attention.

Ingestion:

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give glasses of water, Never give anything by mouth to an unconscious person. If vomiting occurs give further water. Seek immediate medical assistance. Contact a doctor or the Poisons Information Centre immediately.

Medical attention and special treatment:

Treat Symptomatically.

5. FIRE FIGHTING MEASURES

Hazards from combustion products:

Non combustible material. Avoid contact with aluminium and alloys. May give off corrosive fumes upon heating.

Precautions for fire fighters and special protective equipment:

Fire fighters to wear a positive-pressure self-contained breathing apparatus and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots and gloves). Clear fire of all non-emergency personnel. Stay up wind. Keep out of low areas. Eliminate ignition source. Risk of exposure to products of decomposition.

Suitable Extinguishing Media:

Use extinguishing media appropriate to surrounding fire conditions. Remove containers not involved in the fire from vicinity. Fire-fighters should wear full protective clothing including self-contained breathing apparatus.

MATERIAL SAFETY DATA SHEET

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures:

Clear area of all unprotected personnel. Personnel involved in the clean up should wear full protective clothing as described in section 8. Eliminate all sources of ignition. Increase ventilation. Stop leak if safe to do so. Isolate the danger area. Do not let product reach drains or waterways. If product enters sewers or waterways advise local emergency services, or Environmental Protection Authority.

Methods and materials for containment and clean up:

Wear protective equipment to prevent skin and eye contact. Corrosive powder. Oxidizing material. Stop leak if without risk. Absorb with sand or soil, scoop up and place in suitable containers for later treatment/disposal. Use very dilute acid for neutralisation. Dispose of in accordance with local, state and federal regulations at an approved waste disposal facility. Neutralise aqueous solutions with very diluted Hydrochloric Acid. Drain effluent with plenty of water, keeping pH under control. Beware of heat and splashes caused by water reactions (dissolution heat) or neutralisation.

7. HANDLING AND STORAGE

This material must be stored, maintained and used in accordance with the relevant regulations.

Conditions for safe storage:

Keep container tightly closed. Keep container in a cool, well-ventilated area. Separate from acids, alkalis, reducing agents and combustibles.

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols. Keep container dry. Keep away from heat. Keep away from sources of ignition. Keep away from combustible material. Do not ingest. Do not breathe gas/fumes/ vapour/spray. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as reducing agents, combustible materials, organic materials, metals, acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

Worksafe recommends – TWA 2mg/m³ peak limitation.

Engineering controls:

Use in open well ventilated area or provide adequate exhaust ventilation in order to maintain exposure levels below standards if used in closed areas.

Personal Protective Equipment:

Wear full protective clothing, boots, safety goggles, gloves, and a self contained breathing apparatus. Before breaks and at end of work, wash hands and face thoroughly.

MATERIAL SAFETY DATA SHEET

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Granular powder
Colour: white with brown intermitting
Solubility: Miscible in water
Specific Gravity: N/A
Relative Vapour Density (air=1): N/A
Vapour Pressure (20 °C): N/A
Flash Point (°C): N/A
Flammability Limits (%): N/A
Auto Ignition Temperature (°C): N/A
Boiling Point/Range (°C): N/A
pH: 11.8 @ 1% solution

10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure. May start fire in contact with fuels. Reactions with metals can release flammable hydrogen gas.

Conditions to avoid: Store in a cool dry place away from oxidising agents, Acids or products of acid generation. Avoid contact with acids, oxidants, sodium nitrate and sodium nitrite. Avoid Heating.

Incompatible materials: Incompatible with strong oxidising agents, strong acids, organic materials, aluminium, tin, zinc, and nitro compounds.

Hazardous decomposition products: Nature of decomposition products is not known. Material itself is not flammable or explosive but reactions with metal can generate hydrogen gas which is flammable in air (between 4% and 75% volume). May start fires in contact with fuels.

Hazardous reactions: Generally all reactions with acids and halogenated substances are strongly exothermic. It forms explosive products (Chloroacetylenic derivatives) by reacting with Trichloroethylene at warm temperatures. It can cause the decomposition of maleic anhydride at explosive speed. It causes violent polymerisation of acrolein and acrylonitrile. It reacts exothermically with alcohol and chloroform mixtures.

MATERIAL SAFETY DATA SHEET

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Extremely corrosive to skin, causes severe burns to mouth, nausea, intestinal perforation.
Eye contact:	Causes severe burns to eyes.
Skin contact:	Causes severe burns to skin.
Inhalation:	Causes burning and severe irritation.
Long Term Effects:	No information available for the product.
Toxicological Data:	Sodium Hydroxide LD50: Not Available. LC50: Not Available

12. ECOLOGICAL INFORMATION

Ecotoxicity	Do not contaminate waterways.
Persistence and degradability	possible short term degradation products are not likely. However, long term degradation products may arise.

13. DISPOSAL CONSIDERATIONS

Disposal methods:	Dispose of in accordance with all local, state and federal regulations. All empty packaging should be disposed of in accordance with Local, State, and Federal Regulations or recycled/reconditioned at an approved facility.
--------------------------	---

MATERIAL SAFETY DATA SHEET

14. TRANSPORT INFORMATION

Road and Rail Transport

classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; DANGEROUS GOODS.

UN No: 1759

Class-Primary: 8 corrosive

Packing Group: III

Proper Shipping Name: Caustic Alkali Solid N.O.S

Haz chem Code: 2X

Marine Transport

classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No: 1759

Class-Primary: 8 corrosive

Packing Group: III

Proper Shipping Name: Caustic Alkali Solid N.O.S

Hazchem Code: 2X

Air Transport

classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 1759

Class-Primary: 8 corrosive

Packing Group: III

Proper Shipping Name: Caustic Alkali Solid N.O.S

Hazchem Code: 2X

15. REGULATORY INFORMATION

Classification: Hazardous according to criteria of Safe work Australia; HAZARDOUS SUBSTANCE

Hazard Category: Corrosive

Risk Phrases: R35: causes severe burns.
R41: Risk of serious eye damage.

Safety Phrases: S2: Keep out of reach of children.
S3: Keep in a cool place.
S13: Keep away from food, drink and animal foodstuffs.
S14: Keep away from acids, and ammonium salts and other Class 8 corrosive substances.
S23: Do not breathe gas/fumes/vapour/spray
S24/25: Avoid contact with skin and eyes
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S27/28: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.
S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.
S45: In case of accident or if you feel unwell seek medical advice immediately (show label where possible)
S46: If swallowed, seek medical advice immediately and show this container or label

Poisons Schedule: 6

MATERIAL SAFETY DATA SHEET

16. OTHER INFORMATION

This material safety data sheet has been prepared by Midland Chemicals

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Midland Chemicals cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material. If clarification or further information is needed, the user should contact Midland Chemicals at the contact details on page 1.

Midland Chemical's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.